

Script - Deleting a KDE server from the Database

```
DECLARE @ServerID INT, @UPD INT
```

```
SET @ServerID= 1 --Server ID To Delete
```

```
SET @UPD= 0 --0 to Select 1 to Delete
```

```
-- DOT NOT MODIFY BELOW --
```

```
IF @UPD != 1
```

```
BEGIN
```

```
SELECT * FROM [KDG].[dbo].[kdgDelivery] where serverID = @ServerID
```

```
SELECT * FROM [KDG].[dbo].[kdgDeliveryResource] where serverID = @ServerID
```

```
SELECT * FROM [KDG].[dbo].kdgDocument where serverID = @ServerID
```

```
SELECT * FROM [KDG].[dbo].kdgEmailDelivery where serverID = @ServerID
```

```
SELECT * FROM [KDG].[dbo].kdgEmailRecipient where serverID = @ServerID
```

```
SELECT * FROM [KDG].[dbo].kdgPrintDelivery where serverID = @ServerID
```

```
SELECT * FROM [KDG].[dbo].kdgRequest where serverID = @ServerID
```

```
SELECT * FROM [KDG].[dbo].kdgSaveToDiskDelivery where serverID = @ServerID
```

```
SELECT * FROM [KDG].[dbo].kdgServer where ID = @ServerID
```

```
SELECT * FROM [KDG].[dbo].kdgServerConfig where serverID = @ServerID
```

```
END
```

```
IF @UPD = 1
```

```
BEGIN
```

```
DELETE FROM [KDG].[dbo].[kdgDelivery] where serverID = @ServerID
```

```
DELETE FROM [KDG].[dbo].[kdgDeliveryResource] where serverID = @ServerID
```

```
DELETE FROM [KDG].[dbo].kdgDocument where serverID = @ServerID
```

```
DELETE FROM [KDG].[dbo].kdgEmailDelivery where serverID = @ServerID
```

```
DELETE FROM [KDG].[dbo].kdgEmailRecipient where serverID = @ServerID
```

```
DELETE FROM [KDG].[dbo].kdgPrintDelivery where serverID = @ServerID
```

```
DELETE FROM [KDG].[dbo].kdgRequest where serverID = @ServerID
```

```
DELETE FROM [KDG].[dbo].kdgSaveToDiskDelivery where serverID = @ServerID
```

```
DELETE FROM [KDG].[dbo].kdgServer where ID = @ServerID
```

```
DELETE FROM [KDG].[dbo].kdgServerConfig where serverID = @ServerID
```

END

Revision #2

Created 18 July 2025 18:47:12 by Steve Ling

Updated 18 July 2025 18:49:07 by Steve Ling